

2:1 Mini Reels Heat Shrink

1.2-25.4mm Diameter

• Shrink Ratio:	2:1.
• Material:	Polyolefin - Standard wall heat shrink tube.
• Operating Temperature:	-40°C to +135°C.
• Shrink Properties:	Shrinkable temperature: 80°C.
• Features:	Flame retardant, very good chemical and solvent resistance, excellent electrical and physical properties, anti-static, flexible and high dielectric strength. Chemical resistance: Fuel, hydraulic fluid and lubricating oil.
• Application:	Electrical insulation, cable bundling, pipes and wires giving good physical protection.

Standard: UL 224



PLEASE NOTE: Red Heat Shrink Tubing is NOT Halogen Free

Item No.	Colour	Length (m)	Supplied Internal Diameter Min. (mm)	Recovered Internal Diameter Min. (mm)	Wall Thickness After Recovery (mm)
HSM1.2-BLK	Black	12	1.2	0.6	0.36 (±0.10)
HSM1.6-BLK	Black	12	1.6	0.8	0.36 (±0.10)
HSM2.4-BLK	Black	11	2.4	1.2	0.45 (±0.10)
HSM3.2-BLK	Black	11	3.2	1.6	0.45 (±0.10)
HSM4.8-BLK	Black	10	4.8	2.4	0.56 (±0.10)
HSM6.4-BLK	Black	9	6.4	3.2	0.56 (±0.10)
HSM9.5-BLK	Black	7	9.5	4.8	0.56 (±0.10)
HSM12.7-BLK	Black	6	12.7	6.4	0.56 (±0.10)
HSM19.1-BLK	Black	5	19.1	9.5	0.70 (±0.10)
HSM25.4-BLK	Black	3.5	25.4	12.7	0.90 (±0.15)
HSM1.2-BLUE	Blue	12	1.2	0.6	0.36 (±0.10)
HSM1.6-BLUE	Blue	12	1.6	0.8	0.36 (±0.10)
HSM2.4-BLUE	Blue	11	2.4	1.2	0.45 (±0.10)
HSM3.2-BLUE	Blue	11	3.2	1.6	0.45 (±0.10)

2:1 Mini Reels Heat Shrink

1.2-25.4mm Diameter

Item No.	Colour	Length (m)	Supplied Internal Diameter Min. (mm)	Recovered Internal Diameter Min. (mm)	Wall Thickness After Recovery (mm)
HSM4.8-BLUE	Blue	10	4.8	2.4	0.56 (±0.10)
HSM6.4-BLUE	Blue	9	6.4	3.2	0.56 (±0.10)
HSM9.5-BLUE	Blue	7	9.5	4.8	0.56 (±0.10)
HSM12.7-BLUE	Blue	6	12.7	6.4	0.56 (±0.10)
HSM19.1-BLUE	Blue	5	19.1	9.5	0.70 (±0.10)
HSM25.4-BLUE	Blue	3.5	25.4	12.7	0.90 (±0.15)
HSM1.2-CLR	Clear	12	1.2	0.6	0.36 (±0.10)
HSM1.6-CLR	Clear	12	1.6	0.8	0.36 (±0.10)
HSM2.4-CLR	Clear	11	2.4	1.2	0.45 (±0.10)
HSM3.2-CLR	Clear	11	3.2	1.6	0.45 (±0.10)
HSM4.8-CLR	Clear	10	4.8	2.4	0.56 (±0.10)
HSM6.4-CLR	Clear	9	6.4	3.2	0.56 (±0.10)
HSM9.5-CLR	Clear	7	9.5	4.8	0.56 (±0.10)
HSM12.7-CLR	Clear	6	12.7	6.4	0.56 (±0.10)
HSM19.1-CLR	Clear	5	19.1	9.5	0.70 (±0.10)
HSM25.4-CLR	Clear	3.5	25.4	12.7	0.90 (±0.15)
HSM1.2-GRN	Green	12	1.2	0.6	0.36 (±0.10)
HSM1.6-GRN	Green	12	1.6	0.8	0.36 (±0.10)
HSM2.4-GRN	Green	11	2.4	1.2	0.45 (±0.10)
HSM3.2-GRN	Green	11	3.2	1.6	0.45 (±0.10)
HSM4.8-GRN	Green	10	4.8	2.4	0.56 (±0.10)
HSM6.4-GRN	Green	9	6.4	3.2	0.56 (±0.10)
HSM9.5-GRN	Green	7	9.5	4.8	0.56 (±0.10)
HSM12.7-GRN	Green	6	12.7	6.4	0.56 (±0.10)
HSM19.1-GRN	Green	5	19.1	9.5	0.70 (±0.10)
HSM25.4-GRN	Green	3.5	25.4	12.7	0.90 (±0.15)
HSM1.2-RED	Red	12	1.2	0.6	0.36 (±0.10)
HSM1.6-RED	Red	12	1.6	0.8	0.36 (±0.10)
HSM2.4-RED	Red	11	2.4	1.2	0.45 (±0.10)
HSM3.2-RED	Red	11	3.2	1.6	0.45 (±0.10)
HSM4.8-RED	Red	10	4.8	2.4	0.56 (±0.10)
HSM6.4-RED	Red	9	6.4	3.2	0.56 (±0.10)
HSM9.5-RED	Red	7	9.5	4.8	0.56 (±0.10)
HSM12.7-RED	Red	6	12.7	6.4	0.56 (±0.10)
HSM19.1-RED	Red	5	19.1	9.5	0.70 (±0.10)
HSM25.4-RED	Red	3.5	25.4	12.7	0.90 (±0.15)

2:1 Mini Reels Heat Shrink

1.2-25.4mm Diameter

Item No.	Colour	Length (m)	Supplied Internal Diameter Min. (mm)	Recovered Internal Diameter Min. (mm)	Wall Thickness After Recovery (mm)
HSM1.2-WHT	White	12	1.2	0.6	0.36 (±0.10)
HSM1.6-WHT	White	12	1.6	0.8	0.36 (±0.10)
HSM2.4-WHT	White	11	2.4	1.2	0.45 (±0.10)
HSM3.2-WHT	White	11	3.2	1.6	0.45 (±0.10)
HSM4.8-WHT	White	10	4.8	2.4	0.56 (±0.10)
HSM6.4-WHT	White	9	6.4	3.2	0.56 (±0.10)
HSM9.5-WHT	White	7	9.5	4.8	0.56 (±0.10)
HSM12.7-WHT	White	6	12.7	6.4	0.56 (±0.10)
HSM19.1-WHT	White	5	19.1	9.5	0.70 (±0.10)
HSM25.4-WHT	White	3.5	25.4	12.7	0.90 (±0.15)
HSM1.2-YEL	Yellow	12	1.2	0.6	0.36 (±0.10)
HSM1.6-YEL	Yellow	12	1.6	0.8	0.36 (±0.10)
HSM2.4-YEL	Yellow	11	2.4	1.2	0.45 (±0.10)
HSM3.2-YEL	Yellow	11	3.2	1.6	0.45 (±0.10)
HSM4.8-YEL	Yellow	10	4.8	2.4	0.56 (±0.10)
HSM6.4-YEL	Yellow	9	6.4	3.2	0.56 (±0.10)
HSM9.5-YEL	Yellow	7	9.5	4.8	0.56 (±0.10)
HSM12.7-YEL	Yellow	6	12.7	6.4	0.56 (±0.10)
HSM19.1-YEL	Yellow	5	19.1	9.5	0.70 (±0.10)
HSM25.4-YEL	Yellow	3.5	25.4	12.7	0.90 (±0.15)