

2:1 Jumbo Reels Heat Shrink

1.2-101.6mm Diameter

• Shrink Ratio:	2:1.
• Material:	Polyolefin - Standard wall heat shrink tube.
• Operating Temperature:	-55°C to +125°C.
• Shrink Properties:	Shrinkable temperature: 80°C.
• Features:	Flame retardant, very good chemical and solvent resistance, excellent electrical and physical properties, flexible and high dielectric strength. Chemical resistance: Fuel, hydraulic fluid and lubricating oil. UV resistant.
• Application:	Electrical insulation, cable bundling, pipes and wires giving good physical protection.



PLEASE NOTE: Red Heat Shrink Tubing is NOT Halogen Free

Item No.	Colour	Length (m)	Supplied Internal Diameter Min. (mm)	Recovered Internal Diameter Min. (mm)	Wall Thickness After Recovery (mm)
H1.2-BLACK	Black	300	1.2	0.6	0.36 (±0.10)
H1.6-BLACK	Black	300	1.6	0.8	0.36 (±0.10)
H2.4-BLACK	Black	150	2.4	1.2	0.45 (±0.10)
H3.2-BLACK	Black	150	3.2	1.6	0.45 (±0.10)
H4.8-BLACK	Black	60	4.8	2.4	0.56 (±0.10)
H6.4-BLACK	Black	60	6.4	3.2	0.56 (±0.10)
H9.5-BLACK	Black	60	9.5	4.8	0.56 (±0.10)
H12.7-BLACK	Black	60	12.7	6.4	0.56 (±0.10)
H19.1-BLACK	Black	60	19.1	9.5	0.70 (±0.10)
H25.4-BLACK	Black	30	25.4	12.7	0.90 (±0.15)
H38.1-BLACK	Black	30	38.1	19.1	1.00 (±0.15)
H50.8-BLACK	Black	25	50.8	25.4	1.10 (±0.20)
H76.2-BLACK	Black	25	76.2	38.1	1.46 (±0.20)
H101.6-BLACK	Black	25	101.6	50.8	1.46 (±0.20)

2:1 Jumbo Reels Heat Shrink

1.2-101.6mm Diameter

Item No.	Colour	Length (m)	Supplied Internal Diameter Min. (mm)	Recovered Internal Diameter Min. (mm)	Wall Thickness After Recovery (mm)
H2.4-BLUE	Blue	150	2.4	1.2	0.45 (±0.10)
H3.2-BLUE	Blue	200	3.2	1.6	0.45 (±0.10)
H4.8-BLUE	Blue	100	4.8	2.4	0.56 (±0.10)
H6.4-BLUE	Blue	100	6.4	3.2	0.56 (±0.10)
H9.5-BLUE	Blue	100	9.5	4.8	0.56 (±0.10)
H12.7-BLUE	Blue	100	12.7	6.4	0.56 (±0.10)
H19.1-BLUE	Blue	60	19.1	9.5	0.70 (±0.10)
H25.4-BLUE	Blue	30	25.4	12.7	0.90 (±0.15)
H38.1-BLUE	Blue	30	38.1	19.1	1.00 (±0.15)
H50.8-BLUE	Blue	25	50.8	25.4	1.10 (±0.20)
H76.2-BLUE	Blue	25	76.2	38.1	1.46 (±0.20)
H101.6-BLUE	Blue	25	101.6	50.8	1.46 (±0.20)
H4.8-BROWN	Brown	100	4.8	2.4	0.56 (±0.10)
H6.4-BROWN	Brown	60	6.4	3.2	0.56 (±0.10)
H9.5-BROWN	Brown	100	9.5	4.8	0.56 (±0.10)
H12.7-BROWN	Brown	60	12.7	6.4	0.56 (±0.10)
H19.1-BROWN	Brown	60	19.1	9.5	0.70 (±0.10)
H25.4-BROWN	Brown	30	25.4	12.7	0.90 (±0.15)
H38.1-BROWN	Brown	30	38.1	19.1	1.00 (±0.15)
H50.8-BROWN	Brown	25	50.8	25.4	1.10 (±0.20)
H76.2-BROWN	Brown	25	76.2	38.1	1.46 (±0.20)
H101.6-BROWN	Brown	25	101.6	50.8	1.46 (±0.20)
H1.2-CLEAR	Clear	300	1.2	0.6	0.36 (±0.10)
H1.6-CLEAR	Clear	300	1.6	0.8	0.36 (±0.10)
H2.4-CLEAR	Clear	150	2.4	1.2	0.45 (±0.10)
H3.2-CLEAR	Clear	150	3.2	1.6	0.45 (±0.10)
H4.8-CLEAR	Clear	75	4.8	2.4	0.56 (±0.10)
H6.4-CLEAR	Clear	60	6.4	3.2	0.56 (±0.10)
H9.5-CLEAR	Clear	60	9.5	4.8	0.56 (±0.10)
H12.7-CLEAR	Clear	60	12.7	6.4	0.56 (±0.10)
H19.1-CLEAR	Clear	60	19.1	9.5	0.70 (±0.10)
H25.4-CLEAR	Clear	30	25.4	12.7	0.90 (±0.15)
H2.4-GREEN	Green	150	2.4	1.2	0.45 (±0.10)
H3.2-GREEN	Green	200	3.2	1.6	0.45 (±0.10)
H4.8-GREEN	Green	100	4.8	2.4	0.56 (±0.10)
H6.4-GREEN	Green	100	6.4	3.2	0.56 (±0.10)

2:1 Jumbo Reels Heat Shrink

1.2-101.6mm Diameter

Item No.	Colour		Length (m)	Supplied Internal Diameter Min. (mm)	Recovered Internal Diameter Min. (mm)	Wall Thickness After Recovery (mm)
H9.5-GREEN	Green		100	9.5	4.8	0.56 (±0.10)
H12.7-GREEN	Green		100	12.7	6.4	0.56 (±0.10)
H19.1-GREEN	Green		60	19.1	9.5	0.70 (±0.10)
H25.4-GREEN	Green		30	25.4	12.7	0.90 (±0.15)
H3.2-G/Y	Green	Yellow	200	3.2	1.6	0.45 (±0.10)
H4.8-G/Y	Green	Yellow	100	4.8	2.4	0.56 (±0.10)
H6.4-G/Y	Green	Yellow	100	6.4	3.2	0.56 (±0.10)
H9.5-G/Y	Green	Yellow	100	9.5	4.8	0.56 (±0.10)
H12.7-G/Y	Green	Yellow	100	12.7	6.4	0.56 (±0.10)
H19.1-G/Y	Green	Yellow	60	19.1	9.5	0.70 (±0.10)
H25.4-G/Y	Green	Yellow	30	25.4	12.7	0.90 (±0.15)
H38.1-G/Y	Green	Yellow	30	38.1	19.1	1.00 (±0.15)
H50.8-G/Y	Green	Yellow	25	50.8	25.4	1.10 (±0.20)
H76.2-G/Y	Green	Yellow	25	76.2	38.1	1.46 (±0.20)
H101.6-G/Y	Green	Yellow	25	101.6	50.8	1.46 (±0.20)
H4.8-GREY	Grey		100	4.8	2.4	0.56 (±0.10)
H6.4-GREY	Grey		60	6.4	3.2	0.56 (±0.10)
H9.5-GREY	Grey		100	9.5	4.8	0.56 (±0.10)
H12.7-GREY	Grey		100	12.7	6.4	0.56 (±0.10)
H19.1-GREY	Grey		60	19.1	9.5	0.70 (±0.10)
H25.4-GREY	Grey		30	25.4	12.7	0.90 (±0.15)
H38.1-GREY	Grey		30	38.1	19.1	1.00 (±0.15)
H50.8-GREY	Grey		25	50.8	25.4	1.10 (±0.20)
H76.2-GREY	Grey		25	76.2	38.1	1.46 (±0.20)
H101.6-GREY	Grey		25	101.6	50.8	1.46 (±0.20)
H2.4-RED	Red		150	2.4	1.2	0.45 (±0.10)
H3.2-RED	Red		200	3.2	1.6	0.45 (±0.10)
H4.8-RED	Red		100	4.8	2.4	0.56 (±0.10)
H6.4-RED	Red		100	6.4	3.2	0.56 (±0.10)
H9.5-RED	Red		100	9.5	4.8	0.56 (±0.10)
H12.7-RED	Red		100	12.7	6.4	0.56 (±0.10)
H19.1-RED	Red		60	19.1	9.5	0.70 (±0.10)
H25.4-RED	Red		30	25.4	12.7	0.90 (±0.15)
H38.1-RED	Red		30	38.1	19.1	1.00 (±0.15)
H50.8-RED	Red		25	50.8	25.4	1.10 (±0.20)
H76.2-RED	Red		25	76.2	38.1	1.46 (±0.20)

2:1 Jumbo Reels Heat Shrink

1.2-101.6mm Diameter

Item No.	Colour	Length (m)	Supplied Internal Diameter Min. (mm)	Recovered Internal Diameter Min. (mm)	Wall Thickness After Recovery (mm)
H2.4-WHITE	White	150	2.4	1.2	0.45 (±0.10)
H3.2-WHITE	White	150	3.2	1.6	0.45 (±0.10)
H4.8-WHITE	White	75	4.8	2.4	0.56 (±0.10)
H6.4-WHITE	White	60	6.4	3.2	0.56 (±0.10)
H9.5-WHITE	White	60	9.5	4.8	0.56 (±0.10)
H12.7-WHITE	White	60	12.7	6.4	0.56 (±0.10)
H19.1-WHITE	White	60	19.1	9.5	0.70 (±0.10)
H25.4-WHITE	White	30	25.4	12.7	0.90 (±0.15)
H38.1-WHITE	White	30	38.1	19.1	1.00 (±0.15)
H50.8-WHITE	White	25	50.8	25.4	1.10 (±0.20)
H76.2-WHITE	White	25	76.2	38.1	1.46 (±0.20)
H2.4-YELLOW	Yellow	150	2.4	1.2	0.45 (±0.10)
H3.2-YELLOW	Yellow	200	3.2	1.6	0.45 (±0.10)
H4.8-YELLOW	Yellow	100	4.8	2.4	0.56 (±0.10)
H6.4-YELLOW	Yellow	100	6.4	3.2	0.56 (±0.10)
H9.5-YELLOW	Yellow	100	9.5	4.8	0.56 (±0.10)
H12.7-YELLOW	Yellow	100	12.7	6.4	0.56 (±0.10)
H19.1-YELLOW	Yellow	60	19.1	9.5	0.70 (±0.10)
H25.4-YELLOW	Yellow	30	25.4	12.7	0.90 (±0.15)
H38.1-YELLOW	Yellow	30	38.1	19.1	1.00 (±0.15)
H50.8-YELLOW	Yellow	25	50.8	25.4	1.10 (±0.20)
H76.2-YELLOW	Yellow	25	76.2	38.1	1.46 (±0.20)