

# 2:1 Mini Reels Heat Shrink

1.2-25.4mm Diameter

|                                 |                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                             |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| • <b>Shrink Ratio:</b>          | 2:1.                                                                                                                                                                                                                |    |
| • <b>Material:</b>              | Polyolefin - Standard wall heat shrink tube.                                                                                                                                                                        |                                                                                                                                                                                                                                                             |
| • <b>Operating Temperature:</b> | -55°C to +125°C.                                                                                                                                                                                                    |                                                                                                                                                                                                                                                             |
| • <b>Shrink Properties:</b>     | Shrinkable temperature: 80°C.                                                                                                                                                                                       |                                                                                                                                                                                                                                                             |
| • <b>Features:</b>              | Flame retardant, very good chemical and solvent resistance, excellent electrical and physical properties, flexible and high dielectric strength.<br>Chemical resistance: Fuel, hydraulic fluid and lubricating oil. |                                                                                                                                                                                                                                                             |
| • <b>Application:</b>           | Electrical insulation, cable bundling, pipes and wires giving good physical protection.                                                                                                                             |                                                                                                                                                                                                                                                             |



**PLEASE NOTE:** Red Heat Shrink Tubing is NOT Halogen Free

| Item No.    | Colour | Length (m) | Supplied Internal Diameter Min. (mm) | Recovered Internal Diameter Min. (mm) | Wall Thickness After Recovery (mm) |
|-------------|--------|------------|--------------------------------------|---------------------------------------|------------------------------------|
| HSM1.2-BLK  | Black  | 12         | 1.2                                  | 0.6                                   | 0.36 (±0.10)                       |
| HSM1.6-BLK  | Black  | 12         | 1.6                                  | 0.8                                   | 0.36 (±0.10)                       |
| HSM2.4-BLK  | Black  | 11         | 2.4                                  | 1.2                                   | 0.45 (±0.10)                       |
| HSM3.2-BLK  | Black  | 11         | 3.2                                  | 1.6                                   | 0.45 (±0.10)                       |
| HSM4.8-BLK  | Black  | 10         | 4.8                                  | 2.4                                   | 0.56 (±0.10)                       |
| HSM6.4-BLK  | Black  | 9          | 6.4                                  | 3.2                                   | 0.56 (±0.10)                       |
| HSM9.5-BLK  | Black  | 7          | 9.5                                  | 4.8                                   | 0.56 (±0.10)                       |
| HSM12.7-BLK | Black  | 6          | 12.7                                 | 6.4                                   | 0.56 (±0.10)                       |
| HSM19.1-BLK | Black  | 5          | 19.1                                 | 9.5                                   | 0.70 (±0.10)                       |
| HSM25.4-BLK | Black  | 3.5        | 25.4                                 | 12.7                                  | 0.90 (±0.15)                       |
| HSM1.2-BLUE | Blue   | 12         | 1.2                                  | 0.6                                   | 0.36 (±0.10)                       |
| HSM1.6-BLUE | Blue   | 12         | 1.6                                  | 0.8                                   | 0.36 (±0.10)                       |
| HSM2.4-BLUE | Blue   | 11         | 2.4                                  | 1.2                                   | 0.45 (±0.10)                       |
| HSM3.2-BLUE | Blue   | 11         | 3.2                                  | 1.6                                   | 0.45 (±0.10)                       |

# 2:1 Mini Reels Heat Shrink

1.2-25.4mm Diameter

| Item No.     | Colour | Length (m) | Supplied Internal Diameter Min. (mm) | Recovered Internal Diameter Min. (mm) | Wall Thickness After Recovery (mm) |
|--------------|--------|------------|--------------------------------------|---------------------------------------|------------------------------------|
| HSM4.8-BLUE  | Blue   | 10         | 4.8                                  | 2.4                                   | 0.56 (±0.10)                       |
| HSM6.4-BLUE  | Blue   | 9          | 6.4                                  | 3.2                                   | 0.56 (±0.10)                       |
| HSM9.5-BLUE  | Blue   | 7          | 9.5                                  | 4.8                                   | 0.56 (±0.10)                       |
| HSM12.7-BLUE | Blue   | 6          | 12.7                                 | 6.4                                   | 0.56 (±0.10)                       |
| HSM19.1-BLUE | Blue   | 5          | 19.1                                 | 9.5                                   | 0.70 (±0.10)                       |
| HSM25.4-BLUE | Blue   | 3.5        | 25.4                                 | 12.7                                  | 0.90 (±0.15)                       |
| HSM1.2-CLR   | Clear  | 12         | 1.2                                  | 0.6                                   | 0.36 (±0.10)                       |
| HSM1.6-CLR   | Clear  | 12         | 1.6                                  | 0.8                                   | 0.36 (±0.10)                       |
| HSM2.4-CLR   | Clear  | 11         | 2.4                                  | 1.2                                   | 0.45 (±0.10)                       |
| HSM3.2-CLR   | Clear  | 11         | 3.2                                  | 1.6                                   | 0.45 (±0.10)                       |
| HSM4.8-CLR   | Clear  | 10         | 4.8                                  | 2.4                                   | 0.56 (±0.10)                       |
| HSM6.4-CLR   | Clear  | 9          | 6.4                                  | 3.2                                   | 0.56 (±0.10)                       |
| HSM9.5-CLR   | Clear  | 7          | 9.5                                  | 4.8                                   | 0.56 (±0.10)                       |
| HSM12.7-CLR  | Clear  | 6          | 12.7                                 | 6.4                                   | 0.56 (±0.10)                       |
| HSM19.1-CLR  | Clear  | 5          | 19.1                                 | 9.5                                   | 0.70 (±0.10)                       |
| HSM25.4-CLR  | Clear  | 3.5        | 25.4                                 | 12.7                                  | 0.90 (±0.15)                       |
| HSM1.2-GRN   | Green  | 12         | 1.2                                  | 0.6                                   | 0.36 (±0.10)                       |
| HSM1.6-GRN   | Green  | 12         | 1.6                                  | 0.8                                   | 0.36 (±0.10)                       |
| HSM2.4-GRN   | Green  | 11         | 2.4                                  | 1.2                                   | 0.45 (±0.10)                       |
| HSM3.2-GRN   | Green  | 11         | 3.2                                  | 1.6                                   | 0.45 (±0.10)                       |
| HSM4.8-GRN   | Green  | 10         | 4.8                                  | 2.4                                   | 0.56 (±0.10)                       |
| HSM6.4-GRN   | Green  | 9          | 6.4                                  | 3.2                                   | 0.56 (±0.10)                       |
| HSM9.5-GRN   | Green  | 7          | 9.5                                  | 4.8                                   | 0.56 (±0.10)                       |
| HSM12.7-GRN  | Green  | 6          | 12.7                                 | 6.4                                   | 0.56 (±0.10)                       |
| HSM19.1-GRN  | Green  | 5          | 19.1                                 | 9.5                                   | 0.70 (±0.10)                       |
| HSM25.4-GRN  | Green  | 3.5        | 25.4                                 | 12.7                                  | 0.90 (±0.15)                       |
| HSM1.2-RED   | Red    | 12         | 1.2                                  | 0.6                                   | 0.36 (±0.10)                       |
| HSM1.6-RED   | Red    | 12         | 1.6                                  | 0.8                                   | 0.36 (±0.10)                       |
| HSM2.4-RED   | Red    | 11         | 2.4                                  | 1.2                                   | 0.45 (±0.10)                       |
| HSM3.2-RED   | Red    | 11         | 3.2                                  | 1.6                                   | 0.45 (±0.10)                       |
| HSM4.8-RED   | Red    | 10         | 4.8                                  | 2.4                                   | 0.56 (±0.10)                       |
| HSM6.4-RED   | Red    | 9          | 6.4                                  | 3.2                                   | 0.56 (±0.10)                       |
| HSM9.5-RED   | Red    | 7          | 9.5                                  | 4.8                                   | 0.56 (±0.10)                       |
| HSM12.7-RED  | Red    | 6          | 12.7                                 | 6.4                                   | 0.56 (±0.10)                       |
| HSM19.1-RED  | Red    | 5          | 19.1                                 | 9.5                                   | 0.70 (±0.10)                       |
| HSM25.4-RED  | Red    | 3.5        | 25.4                                 | 12.7                                  | 0.90 (±0.15)                       |

# 2:1 Mini Reels Heat Shrink

1.2-25.4mm Diameter

| Item No.    | Colour | Length (m) | Supplied Internal Diameter Min. (mm) | Recovered Internal Diameter Min. (mm) | Wall Thickness After Recovery (mm) |
|-------------|--------|------------|--------------------------------------|---------------------------------------|------------------------------------|
| HSM1.2-WHT  | White  | 12         | 1.2                                  | 0.6                                   | 0.36 (±0.10)                       |
| HSM1.6-WHT  | White  | 12         | 1.6                                  | 0.8                                   | 0.36 (±0.10)                       |
| HSM2.4-WHT  | White  | 11         | 2.4                                  | 1.2                                   | 0.45 (±0.10)                       |
| HSM3.2-WHT  | White  | 11         | 3.2                                  | 1.6                                   | 0.45 (±0.10)                       |
| HSM4.8-WHT  | White  | 10         | 4.8                                  | 2.4                                   | 0.56 (±0.10)                       |
| HSM6.4-WHT  | White  | 9          | 6.4                                  | 3.2                                   | 0.56 (±0.10)                       |
| HSM9.5-WHT  | White  | 7          | 9.5                                  | 4.8                                   | 0.56 (±0.10)                       |
| HSM12.7-WHT | White  | 6          | 12.7                                 | 6.4                                   | 0.56 (±0.10)                       |
| HSM19.1-WHT | White  | 5          | 19.1                                 | 9.5                                   | 0.70 (±0.10)                       |
| HSM25.4-WHT | White  | 3.5        | 25.4                                 | 12.7                                  | 0.90 (±0.15)                       |
| HSM1.2-YEL  | Yellow | 12         | 1.2                                  | 0.6                                   | 0.36 (±0.10)                       |
| HSM1.6-YEL  | Yellow | 12         | 1.6                                  | 0.8                                   | 0.36 (±0.10)                       |
| HSM2.4-YEL  | Yellow | 11         | 2.4                                  | 1.2                                   | 0.45 (±0.10)                       |
| HSM3.2-YEL  | Yellow | 11         | 3.2                                  | 1.6                                   | 0.45 (±0.10)                       |
| HSM4.8-YEL  | Yellow | 10         | 4.8                                  | 2.4                                   | 0.56 (±0.10)                       |
| HSM6.4-YEL  | Yellow | 9          | 6.4                                  | 3.2                                   | 0.56 (±0.10)                       |
| HSM9.5-YEL  | Yellow | 7          | 9.5                                  | 4.8                                   | 0.56 (±0.10)                       |
| HSM12.7-YEL | Yellow | 6          | 12.7                                 | 6.4                                   | 0.56 (±0.10)                       |
| HSM19.1-YEL | Yellow | 5          | 19.1                                 | 9.5                                   | 0.70 (±0.10)                       |
| HSM25.4-YEL | Yellow | 3.5        | 25.4                                 | 12.7                                  | 0.90 (±0.15)                       |