Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Reference number: SDS00011

Issue date: 5/7/2024 Revision date: 2/20/2025 Supersedes version of: 8/13/2024 Version: 1.3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Product name	: WHITE GREASE
Vaporizer	: Aerosol
Product group	: End product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses Use of the substance/mixture

: Lubricants, Greases and Release Products

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Beal (UK) Ltd Sterling Works Texas Street Leeds, LS27 0HG United Kingdom T +44 (0)113 253 8888 Sales@beal.org.uk

1.4. Emergency telephone number

Emergency number

: +44(0) 113 253 8888

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] Aerosol, Category 1 H222;H229

Skin corrosion/irritation, Category 2	H315
Specific target organ toxicity – Single exposure, Category 3,	H336
Narcosis	
Hazardous to the aquatic environment – Chronic Hazard,	H411
Category 2	
Full text of H- and EUH-statements: see section 16	

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/	2008 [CLP]
Hazard pictograms (CLP)	
	GHS02 GHS07 GHS09
Signal word (CLP)	: Danger
Contains	: N-HEXANE; HYDROCARBONS C6-C7, N-ALKANES, ISOALKANES, CYCLICS
Hazard statements (CLP)	: H222 - Extremely flammable aerosol.
	H229 - Pressurised container: May burst if heated.
	H315 - Causes skin irritation.
	H336 - May cause drowsiness or dizziness.
	H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
	No smoking.
	P211 - Do not spray on an open flame or other ignition source.
	P251 - Do not pierce or burn, even after use.
	P261 - Avoid breathing vapours, spray.
	P271 - Use only outdoors or in a well-ventilated area.
	P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P280 - Wear protective gloves.
	P302+P352 - IF ON SKIN: Wash with plenty of soap and water.
	P312 - Call a POISON CENTER, doctor if you feel unwell.
	Dispose of in accordance with relevant local regulations.
	P102 - Keep out of reach of children.

2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS substance with national workplace exposure limit(s) (GB)	CAS-No.: 68476-85-7 EC-No.: 270-704-2 REACH-no: 2119463258-33- XXXX	≥ 50	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
HYDROCARBONS C6-C7, N-ALKANES, ISOALKANES, CYCLICS	EC-No.: 921-024-6 PART*	≥ 20 – < 50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ZINC OXIDE	CAS-No.: 1314-13-2 EC-No.: 215-222-5 EC Index-No.: 030-013-00-7	≥ 1 – < 5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
N-HEXANE substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 110-54-3 EC-No.: 203-777-6	≥1-<5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361f STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case. Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	 Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do NOT induce vomiting. Obtain emergency medical attention.
4.2. Most important symptoms and effect	ts, both acute and delayed
Symptoms/effects after inhalation	: May cause drowsiness or dizziness. Inhalation may cause irritation (cough, short breathing, difficulty in breathing).
Symptoms/effects after skin contact	: Causes skin irritation. Repeated exposure may cause skin dryness or cracking. Contact with the liquefied gas may cause frostbite.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media Unsuitable extinguishing media	Dry powder. Foam. Carbon dioxide. Water fog.Do not use a water jet since it may cause the fire to spread.
5.2. Special hazards arising from the substa	ance or mixture
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	 Extremely flammable aerosol. Pressurised container: May burst if heated. May form flammable/explosive vapour-air mixture. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. Toxic fumes may be released.
5.3. Advice for firefighters	
Precautionary measures fire	: Eliminate all ignition sources if safe to do so. Evacuate area. Fight fire remotely due to the risk of explosion. Cool down the containers exposed to heat with a water spray.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Protection during firefighting

: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures		
6.1. Personal precautions, prote	ective equipment and emergency procedures	
6.1.1. For non-emergency personnel		
Protective equipment Emergency procedures	Ensure there is adequate ventilation.Ventilate spillage area. No open flames, no sparks, and no smoking.	
6.1.2. For emergency responders		
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".	
6.2. Environmental precautions		

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up		
For containment Methods for cleaning up Other information	 Remove all sources of ignition. Absorb remaining liquid with sand or inert absorbent and remove to safe place. Dispose of materials or solid residues at an authorized site. 	
6.4. Reference to other sections		

For further information refer to section 13.

SECTION 7: Handling and storage			
7.1. Precautions for safe handling			
u u u u u u u u u u u u u u u u u u u	Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.		
7.2. Conditions for safe storage, including an	y incompatibilities		
Storage conditions :	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool.		

7.3. Specific end use(s)

For further information refer to section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

N-HEXANE (110-54-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	n-Hexane
IOEL TWA	72 mg/m³
IOEL TWA [ppm]	20 ppm

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

N-HEXANE (110-54-3)		
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC	
United Kingdom - Occupational Exposure Limits		
Local name	n-Hexane	
WEL TWA (OEL TWA) [1]	72 mg/m³	
WEL TWA (OEL TWA) [2]	20 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (68476-85-7)		
United Kingdom - Occupational Exposure Limits		
Local name	Liquefied petroleum gas	
WEL TWA (OEL TWA) [1]	1750 mg/m³	
WEL TWA (OEL TWA) [2]	1000 ppm	
WEL STEL (OEL STEL)	2180 mg/m ³	
WEL STEL (OEL STEL) [ppm]	1250 ppm	
Remark	Carc (Capable of causing cancer and/or heritable genetic damage (only applies if LPG contains more than 0.1% of buta-1,3-diene))	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection: Safety glasses

Eye protection			
Туре	Field of application	Characteristics	Standard
Safety goggles	Droplet	Plastic	EN 166

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR), Neoprene rubber (HNBR)				EN 374-2

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

inid rol to th

Avoid release to the environment.		
SECTION 9: Physical and chemical p	roperties	
9.1. Information on basic physical and chemical properties		
Physical state	: Liquid	
Colour	: white. off-white.	
Appearance	: Aerosol.	
Odour	: characteristic.	
Odour threshold	: Not available	
Melting point	: Not applicable	
Freezing point	: Not available	
Boiling point	: Not available	
Flammability	: Extremely flammable aerosol.	
Explosive properties	: Pressurised container: May burst if heated.	
Lower explosion limit	: Not available	
Upper explosion limit	: Not available	
Flash point	: < -40 °C Data stated for propellant.	
Auto-ignition temperature	: 410 – 580 °C Data stated for propellant.	
Decomposition temperature	: Not available	
рН	: Not available	
Viscosity, kinematic	: Not available	
Solubility	: Not available	
Partition coefficient n-octanol/water (Log Kow)	: Not available	
Vapour pressure	: 590 – 1760 hPa @45 degrees Centigrade. Data stated for propellant.	
Vapour pressure at 50°C	: Not available	
Density	: Not available	
Relative density	: Not available	
Relative vapour density at 20°C	: Not available	
Particle characteristics	: Not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients

: 77.147285 %

9.2.2. Other safety characteristics

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Direct sunlight.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regula	tion (EC	C) No 1272/2008
--	----------	-----------------

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
N-HEXANE (110-54-3)	
STOT-single exposure	May cause drowsiness or dizziness.
HYDROCARBONS C6-C7, N-ALKANES, ISO	ALKANES, CYCLICS
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
N-HEXANE (110-54-3)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
PETROLEUM GASES, LIQUEFIED; PETROL	EUM GAS (68476-85-7)
LOAEC (inhalation, rat, gas, 90 days)	12000 ppm Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:
Aspiration hazard	Not classified
WHITE GREASE	
Vaporizer	Aerosol

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general Hazardous to the aquatic environment, short–term (acute) Hazardous to the aquatic environment, long–term (chronic) Not rapidly degradable	 Harmful to aquatic life. Not classified Toxic to aquatic life with long lasting effects.
12.2. Persistence and degradability	
No additional information available	
12.3. Bioaccumulative potential	
No additional information available	
12.4. Mobility in soil	
No additional information available	
12.5. Results of PBT and vPvB assessment	
No additional information available	
12.6. Endocrine disrupting properties	
No additional information available	
12.7. Other adverse effects	
Other adverse effects	: Volatile Organic Compounds (VOC).

SECTION 13: Disposal considerations

13.1. Waste treatment methods	
Waste treatment methods HP Code	 Comply with local regulations for disposal. HP3 - "Flammable:" flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration. HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

n accordance with ADR / IMD)G / IATA / ADN / RID			
ADR	IMDG	ΙΑΤΑ	ADN	RID
14.1. UN number or ID n	umber			
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping	g name			
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document descr	iption			
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONME NTALLY HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1 ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard o	class(es)			
2.1	2.1	2.1	2.1	2.1
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental haz	ards		•	
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 11
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP200
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading	: CV9, CV12
and handling (ADR)	
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D
Transport by sea	
Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69
Air transport	
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L
Inland waterway transport	
Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1
Rail transport	
Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acr	onyms:
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
РВТ	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:		
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Asp. Tox. 1	Aspiration hazard, Category 1	
Flam. Gas 1A	Flammable gases, Category 1A	
Flam. Liq. 2	Flammable liquids, Category 2	
H220	Extremely flammable gas.	
H222	Extremely flammable aerosol.	
H225	Highly flammable liquid and vapour.	
H229	Pressurised container: May burst if heated.	
H280	Contains gas under pressure; may explode if heated.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H336	May cause drowsiness or dizziness.	
H361f	Suspected of damaging fertility.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
Press. Gas (Liq.)	Gases under pressure : Liquefied gas	
Repr. 2	Reproductive toxicity, Category 2	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.