MATERIAL SAFETY DATA SHEET

LAST REV. DATE : 26/07/07 SHEET 1 of 2

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY NAME

PRODUCT NAME:

ALUMINIUM ANTISEIZE COMPOUND

PRODUCT CODE:

LS159

COMPANY NAME:

Beal UK Ltd

Sterling Works, Texas St

Tingley, Leeds LS27 0HG

Tel: +44 (0)113 253 8888 Fax: +44 (0)113 253 0223 e-mail: sales@beal.org.uk

2. HAZARDS IDENTIFICATION

MAIN HAZARDS: Not classified as hazardous

3. COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS: SOLVENT REFINED MINERAL OIL 30 - 60%. CAS: 64742-62-7

4. FIRST AID MEASURES

EYE CONTACT: Wash out eye with plenty of water. Obtain medical attention if soreness

or redness persists

SKIN CONTACT: Wash skin with soap and water. If grease has been injected under the skin,

seek Medical advice immediately.

INGESTION: Do not induce vomiting. Obtain medical attention

INHALATION: Provide rest, warmth and fresh air.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use water Spray to cool containers. Use foam, dry chemical, carbon

dioxide or suitable extinguishing media..

EXPOSURE HAZARDS: This product may give rise to hazardous fumes in a fire.

PROTECTION FOR FIRE- FIGHTERS: Wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Refer to section 8 for personal protection details

SPILLAGES: Transfer into suitable containers for recovery or disposal.

7. HANDLING AND STORAGE

HANDLING: Avoid direct contact with the substance.

STORAGE: Store in cool well ventilated area

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE EQUIPMENT:





HAZARDOUS INGREDIANTS: SOLVENT REFINES BASE OIL. TWA (8 Hr exposure limit): 5mg/m³ STEL

(15min exposure limit): 10mg/m³ (OES)

HAND PROTECTION: PVC gloves

EYE PROTECTION: Wear approved safety goggles

BODY PROTECTION: Normal work wear

RESPIRATORY PROTECTION: Not normally required

<u>LAST REV. DATE</u>: 26/07/07 SHEET 2 of 2

ALUMINIUM ANTISEIZE

MATERIAL SAFETY DATA SHEET

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Smooth Grease

COLOUR: Silver Gray

ODOUR: Odourless.

MELTING POINT (°C): Melts above 200
FLASH POINT (PMCC) (°C): Exceed 200.

SOLUBILITY IN WATER (KG/M3): Insoluble.

DENSITY (KG/M3): 1.02 (Measured as kg/litre)

AUTO-FLAMMABILITY (°C): Above 200.

10. STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions.

CONDITIONS TO AVOID: Heat.

MATERIALS TO AVOID: Strong oxidising agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion will generate: smoke, carbon dioxide and carbon monoxide

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY Low order of acute toxicity.

12. ECOLOGICAL INFORMATION

MOBILITY: Non volatile. The product is poorly absorbed onto soils or sediments.

PERSISTENCE & DEGRADABILITY: Only slightly biodegradable.

BIO-ACCUMULATION: Product is not expected to bio-accumulate.

13. DISPOSAL RECOMMENDATIONS

PRODUCT DISPOSAL: Dispose in a regulated landfill site or other method for hazardous or toxic

waste. Dispose of in accordance with local and national regulations.

14. TRANSPORT INFORMATION

UN CLASS: Not classified.

ADR/RID – CLASS: Not classified.

IMDG – CLASS: Not classified.IATA – CLASS: Not classified.

15. REGULATORY INFORMATION

HAZARD SYMBOLS: No significant hazard.

R PHRASES: NONE. S PHRASES: NONE.

16. OTHER INFORMATION

PRODUCT USE: For industrial use only. Lubricant.

EC Directive 91/155/EEC defining the laying down and detailed arrangements for the system of specific information relating to Dangerous Preparations Directive – 2001/58/EC. EC Directive 88/379/EEC relating to the classification, packaging and labelling of dangerous preparations.

To the best of our knowledge, the information contained herein is accurate. Although certain hazards may be described we cannot predict that these are the only hazards, or combination of hazards, that may exist in a workplace. This MSDS, therefore, forms a component only of a risk assessment carried out by, or on behalf of, the user.