PRODUCT SAFETY DATA SHEET

1. Identification of the Substance/Preparation & Supplier.

Product Name:	LS161 Penetrant Universal Citrus PTFE T1250
Product Type:	Penetrating Oil
Supplier:	Beal UK Ltd, Texas Street, Tingley (A650), Leeds. LS27 0HG
Emergency information:	Emergency phone number (Office hours only): 0113 253 8888 Fax no: 0113 253 0223

2. Hazards Identification.

Hazard designation: Xn Harmful

Information pertaining to particular dangers for man and environment:

- R65: Harmful: may cause lung damage if swallowed
- R66: Repeated exposure may cause skin dryness or cracking

Classification system:

The health and environmental hazards of this preparation have been assessed by the conventional method described In annex II and III of the preparations Directive 1999/45 EC.

3. Composition/Information on Ingredients.

Hazardous component:	EINECS	Cas No.	Index	Risk Phrases:	Concentration:
Petroleum Distillate	265-149-8	64742-47-8	Xn	R65, R66	50-80%
Diacetone Alcohol	204-626-7	123-42-2	Xi	R36	5-15%

Additional information: For the wording of the listed risk phrases refer to section 16.

4. First Aid Measures.

Immediate medical attention is required.

Eye Contact: Flush with clean water for 15minutes. If irritation persists, obtain medical attention.

- Skin Contact: Wash off with soap and water. The application of skin reconditioning (emollient) cream, can be beneficial.
- **Inhalation:** Remove to fresh air. If symptoms persist, seek medical advice.
- Ingestion: Water to drink and rinse may be beneficial. Aspiration Hazard. May cause rapid absorption via lungs, resulting in injury to other body systems. Do not induce vomiting without medical advice.

5. Fire Fighting Measures:

Suitable Extinguishing Media: Foam, Dry Powder, Co2, Sand, Earth, Fine Water Spray suitable.

Unsuitable Extinguishing Media for Reasons of Safety: Fire exposed containers should be sprayed with water to keep cool and avoid bursting.

T1250	REVISION 1	19.11.2010	Page 1

Special Hazards caused by the material, its products of combustion or flue gases: Not classed as flammable but, inherently combustible. If involved in fire, may evolve noxious fumes.

Protective Equipment: Self-contained breathing apparatus may be required.

6. Accidental Release Measures.

Personal safety precautions: Remove ignition sources. Wear protective equipment. Keep unprotected persons away. Use protective clothing, chemical eye goggles and PVC or rubber gloves.

Measures for environmental protection: Do not allow product to soak into drains or water courses. Inform authorities in case of contamination of water or sewage system.

Methods for cleaning/collecting: Soak liquid in absorbent material and collect solids in a container. Wash down floor area as spillages can be slippery.

Dispose only in accordance with Local Authority regulations, via authorised waste disposal agent. Advice can be obtained from the Waste Regulation Authority whether special waste regulations apply to this product.

7. Handling and Storage.

Handling:

Information for safe handling: Keep in tightly closed containers. Take note of emission threshold.

Storage:

Requirements to be met by storerooms and containers: Store between 10-35°C. Store in mild steel, stainless steel or polyethylene containers.

Information about storage in a common storage facility: Store in a cool dry place away from heat or sources of combustion.

Specific Uses: To be used as a Penetrating Fluid, Lubricant & Dewatering Rust Preventive.

8. Exposure Controls/Personal Protection.

Exposure limit values:

Ingredient Name		8hr TWA	15min STEL
Petroleum Distillates	WEL	5mg/m3	10mg/m3
Diacetone Alcohol	WEL	50ppm	75ppm

Occupational exposure controls:

Respiratory Protection:	Unlikely to be necessary. Avoid breathing mists or vapours.
Hand:	PVC or rubber gloves are recommended.
Eyes:	Safety eye goggles should be worn.
Skin:	Use protective clothing. Remove contaminated clothing and wash with soap and water.

Environmental exposure controls:

Dispose only in accordance with Local Authority regulations, via authorised waste disposal agent.

9. Physical and Chemical Properties.

Appearance:	Clear Pale Fluid
Odour:	Cinnamon
Flash Point:	>65°C
Water Solubility:	Immiscible
Viscosity @ 40°C:	<7.0c/st
Specific Gravity @ 20°C:	0.820 typical
Solubility in Organics:	Soluble in many
- •	-

T1250	REVISION 1	19.11.2010	Page 2

10. Stability and Reactivity.

Conditions to Avoid: Protect against naked flames, hot surfaces and other high temperature sources.

Materials to Avoid: Strong oxidising agents.

Hazardous Decomposition Products: Oxides of carbon, water vapour and unidentified organic and inorganic compounds, some of which may be toxic may be produced. Product is stable under normal conditions.

<u>11. Toxicological Information.</u>

Toxic Dose LD50 Oral (rat) 5000mg/kg

- Eyes: Likely to cause temporary irritation and stinging.
- Skin: Prolonged or repeated contact may lead to de-fatting of the skin and/or slight irritation.
- Inhalation: Excessive exposure to mists caused by atomising systems may cause irritation to eyes and respiratory tract, possibly inflammation of the lungs.
- Ingestion: Aspiration Hazard. May cause lung damage if material gets into lungs after swallowing, breathing vapour/spray or vomiting swallowed material. Swallowing of small amounts is not likely to cause serious discomfort. If swallowed in larger quantities, may cause vomiting and diarrhoea.

12. Ecological Information.

Eco-toxicity: Hazardous to aquatic life.

Mobility: The product should not be allowed to enter drains or watercourses or be deposited where it can affect ground or surface waters. Avoid transfer into the environment.

Persistence and Degradability: Product is readily biodegradable.

Bio-accumulative Potential: Not expected to bio-accumulate.

13. Disposal Recommendations.

Product should be disposed of via an authorised waste disposal contractor in accordance with all local and national regulations.

Dispose of empty containers in accordance with local and national regulations.

Advice can be obtained from the Waste Regulation Authority whether special waste regulations apply to this product.

14. Transport Information.

Product is not classified as hazardous for transport.

15. Regulatory Information.

Designation according to EC guidelines:

The product has been classified and labelled in accordance with EC Directives / Ordinance on Hazardous Materials (CHIP).

Hazard Symbol:



Classification:	Xn	Harmful
Risk Phrases:	R65: R66:	Harmful: may cause lung damage if swallowed Repeated exposure may cause skin dryness or cracking

T1250	REVISION 1	19.11.2010	Page 3

Safety Phrases:	S24/25: S37: S43: S62:	Avoid contact with skin and eyes Wear suitable gloves In case of fire use foam/dry powder/CO2 – fine water spray suitable If swallowed, do not induce vomiting, seek medical advice and show this container or label.
-----------------	---------------------------------	---

National Regulations:

Regulations which may apply in event of accident: Control of Major Accident Hazards (COMAH)

Critical quantity values according to the regulations on accidents should be adhered to.

16. Other Information.

Do not mix with other chemicals.

The information provided in this data sheet has been compiled in accordance with the requirements of the Chemicals (Hazard information and packaging) Regulations 2009 (CHIP 4).

This data sheet does not constitute an assessment of the workplace risks as required under the provisions of the Health & Safety at Work act and the Control of Substances Hazardous to Health (COSHH).

R-phrases relevant to the products hazardous ingredients:

- R36: Irritating to the eyes
- R65: Harmful: may cause lung damage if swallowed
- R66: Repeated Exposure may cause skin dryness or cracking

Training Advice: Users should be trained in good industrial hygiene practise.

Recommended Restrictions on Use:

*Date compared to the previous version altered.

Legal Disclaimer:

The information supplied above is based upon the present state of our knowledge of the product at the time of publication. It is given in good faith and no warranty is implied with respect to the specification or quality of the product. The user must satisfy himself that the product is entirely suitable for his purpose.