SAFETY DATA SHEET Sterling Flammable Air Duster

SECTION 1: Identification of the substance/mixture and of the company/undertaking		
1.1. Product identifier		
Product name	Sterling Flammable Air Duster	
Product number	LS172	
1.2. Relevant identified uses o	f the substance or mixture and uses advised against	
Identified uses	Duster Spray	
1.3. Details of the supplier of the supplier of the supplier of the supplier of the supplication of the su	he safety data sheet	
Supplier	Beal (UK) Ltd	
	Sterling Works	
	Texas Street	
	Tingley (A650)	
	Leeds, West Yorkshire	
	LS27 0HG	
	T 0113 253 8888	
	F 0113 253 0223	
	sales@beal.org.uk	
1.4. Emergency telephone number		
Emergency telephone	0113 253 8888	
SECTION 2: Hazards identification		
2.1. Classification of the substance or mixture		
Classification		
Physical hazards	Aerosol 1 - H222, H229	
Health hazards	Not Classified	
Environmental hazards	Not Classified	
Classification (67/548/EEC or 1999/45/EC)	F+;R12.	
Human health	Gas or vapour is harmful on prolonged exposure or in high concentrations. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.	
Environmental	This product does not contain substances which are harmful to aquatic organisms or which may cause long term effects to the aquatic environment	
Physicochemical	Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.	
2.2. Label elements		
Dista ano as		

Pictogram



Signal word	Danger
Hazard statements	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated
Precautionary statements	 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P102 Keep out of reach of children. P260 Do not breathe vapour/spray. P271 Use only outdoors or in a well-ventilated area. P501 Dispose of contents/container in accordance with local regulations.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2.	Mixtures

PETROLEUM GASES, LIQUEFIED; F	'ETROLEUM GAS	60-100%
CAS number: 68476-85-7	EC number: 270-704-2	
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Gas 1 - H220	F+;R12 Carc. Cat. 1;R45 Muta. Cat. 2;R46	
Press. Gas, Liquefied - H280		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

4.1. Description of first aid me General information Inhalation	Move affected person to fresh air at once. If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately. Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention.
Inhalation	If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.
	keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention.
•	
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.
4.2. Most important symptom	ns and effects, both acute and delayed
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
4.3. Indication of any immedi	iate medical attention and special treatment needed
Notes for the doctor	Treat symptomatically.
SECTION 5: Firefighting mea	asures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

5.2. Special hazards arising from the substance or mixture Specific hazards Extremely flammable. Forms explosive mixtures with air. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Containers can burst violently or explode when heated, due to excessive pressure buildup. 5.3. Advice for firefighters Protective actions during Cool containers exposed to heat with water spray and remove them from the fire area if it can firefighting be done without risk. Use water to keep fire exposed containers cool and disperse vapours. Warn firefighters that aerosols are involved. SECTION 6: Accidental release measures 6.1. Personal precautions, protective equipment and emergency procedures Personal precautions Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate. Avoid inhalation of vapours. 6.2. Environmental precautions Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material. 6.3. Methods and material for containment and cleaning up Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion. 6.4. Reference to other sections Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13. **SECTION 7: Handling and storage** 7.1. Precautions for safe handling Usage precautions Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Do not spray on a naked flame or any incandescent material. 7.2. Conditions for safe storage, including any incompatibilities Storage precautions Extremely flammable. Keep away from heat, sparks and open flame. Store at moderate temperatures in dry, well ventilated area. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. 7.3. Specific end use(s) Specific end use(s) The identified uses for this product are detailed in Section 1.2. SECTION 8: Exposure Controls/personal protection 8.1. Control parameters Occupational exposure limits PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³

Short-term exposure limit (8-nour 1 WA): WEL 1000 ppm 1750 mg/m³ WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Appropriate engineering controls	Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients.
Personal protection	When using do not smoke.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.
Hand protection	Due to the packaging form, aerosol, risk of skin contact is small. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.
Hygiene measures	Wash hands after handling. Wash promptly if skin becomes contaminated. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Use appropriate skin cream to prevent drying of skin.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Colourless.
Odour	Odourless.
Initial boiling point and range	-40 to -2°C @ 1013 hPa
Flash point	<-40°C
Upper/lower flammability or explosive limits	Lower : 1.8% - Upper 9.5%
Vapour pressure	ca. 590 to 1760 kPa @ 45°C
Vapour density	ca. 1.5 at 15°C
Partition coefficient	log Pow: ca. 2.3 to 2.8
Auto-ignition temperature	410-580°C
Comments	Information given is applicable to the major ingredient.
9.2. Other information	
Other information	Not available.
Volatile organic compound	This product contains a maximum VOC content of 533 g/l.
SECTION 10: Stability and reactivity	
10.1. Reactivity	
Reactivity	Stable at normal ambient temperatures and when used as recommended.
10.2. Chemical stability	
Stability	Avoid the following conditions: Heat, sparks, flames.
10.3. Possibility of hazardous reactions	

Possibility of hazardous reactions	Does not decompose when used and stored as recommended.	
10.4. Conditions to avoid		
Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.	
10.5. Incompatible materials		
Materials to avoid	Keep away from oxidising materials, heat and flames.	
10.6. Hazardous decomposition products		
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours.	
SECTION 11: Toxicological information		
11.1. Information on toxicological effects		

General information	Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.
Inhalation	In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Unconsciousness, possibly death.
Skin contact	Skin irritation should not occur when used as recommended. Repeated exposure may cause skin dryness or cracking.
Eye contact	Vapour or spray in the eyes may cause irritation and smarting.
Acute and chronic health hazards	Arrhythmia (deviation from normal heart beat). In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea.
Route of entry	Inhalation
Target organs	Central nervous system Respiratory system, lungs
Medical symptoms	Arrhythmia (deviation from normal heart beat). Narcotic effect. Vapours may cause drowsiness and dizziness.

SECTION 12: Ecological Information

I

Ecotoxicity	No negative effects on the aquatic environment are known. The product is not expected to be toxic to aquatic organisms.	
12.1. Toxicity		
Toxicity	Not available.	
12.2. Persistence and degradability		
Persistence and degradability	Not available.	
12.3. Bioaccumulative potential		
Bioaccumulative potential	Not available.	
Partition coefficient	log Pow: ca. 2.3 to 2.8	
12.4. Mobility in soil		
Mobility	Not known.	

12.5. Results of PBT and vPvB assessment	
Results of PBT and vPvB assessment	Not available.
12.6. Other adverse effects	
Other adverse effects	Not available.
SECTION 13: Disposal consid	erations
13.1. Waste treatment method	<u>s</u>
General information	Do not puncture or incinerate, even when empty.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Empty containers must not be punctured or incinerated because of the risk of an explosion.
SECTION 14: Transport inform	nation
General	This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities. Aerosols not so packed and labelled must show the following.
14.1. UN number	
UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
14.2. UN proper shipping name	e
Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS
14.3. Transport hazard class(e	<u>es)</u>
ADR/RID class	2.1
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
Transport labels	

14.4. Packing group Not applicable.

2

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant No.

14.6. Special precautions for user

EmS

F-D, S-U

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EU legislation	Commission Regulation (EU) No 453/2010 of 20 May 2010.
Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131. British Aerosol Manufacturers Code of Practice 7th. Edition 1999

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	Supplemental information added.
Revision date	18/11/2015
Revision	2
SDS number	12839
SDS status	Approved.
Risk phrases in full	R12 Extremely flammable.
Hazard statements in full	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.