

SAFETY DATA SHEET

Sterling Engine Degreaser

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Sterling Engine Degreaser

Product number LS180

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Degreasing spray PC35 Washing and cleaning products

1.3. Details of the supplier of the safety data sheet

Supplier Beal (UK) Ltd
Sterling Works
Texas Street
Tingley (A650)
Leeds, West Yorkshire
LS27 0HG
T 0113 253 8888
F 0113 253 0223
sales@beal.org.uk

1.4. Emergency telephone number

Emergency telephone 0113 253 8888

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

Health hazards Eye Irrit. 2 - H319 STOT RE 1 - H372

Environmental hazards Aquatic Chronic 3 - H412

Classification (67/548/EEC or 1999/45/EC) F+;R12. N;R51/53.

Environmental This product contains substances which are very toxic or toxic to aquatic organisms and may cause long term effects to the aquatic environment (see sections 2 and 12)

2.2. Label elements

Pictogram



Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated
H319 Causes serious eye irritation.
H372 Causes damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Sterling Engine Degreaser

Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.</p> <p>P102 Keep out of reach of children.</p> <p>P260 Do not breathe vapour/ spray.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P501 Dispose of contents/ container in accordance with local regulations.</p>
---------------------------------	---

Supplemental label information	RCH002b For professional users only.
---------------------------------------	--------------------------------------

Contains	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
-----------------	--

Detergent labelling	≥ 30% aliphatic hydrocarbons, < 5% non-ionic surfactants
----------------------------	--

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS		30-60%
CAS number: 68476-85-7	EC number: 270-704-2	
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Gas 1 - H220	F+;R12 Carc. Cat. 1;R45 Muta. Cat. 2;R46	
Press. Gas, Liquefied - H280		
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)		30-60%
CAS number: —	EC number: 919-164-8	REACH registration number: 01-2119473977-17-XXXX
Classification	Classification (67/548/EEC or 1999/45/EC)	
STOT RE 1 - H372	Xn;R65. Xi;R38. N;R51/53. R10.	
Asp. Tox. 1 - H304		
Aquatic Chronic 3 - H412		
Alcohol ethoxylate		1-5%
CAS number: 68439-46-3	REACH registration number: N/A	
Classification	Classification (67/548/EEC or 1999/45/EC)	
Acute Tox. 4 - H302	Xn;R22. Xi;R41.	
Eye Dam. 1 - H318		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air at once.
----------------------------	--

Sterling Engine Degreaser

Inhalation	If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly with water. DO NOT induce vomiting. Get medical attention immediately.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
----------------------------	---

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog.
-------------------------------------	--

5.2. Special hazards arising from the substance or mixture

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up. Extremely flammable. Forms explosive mixtures with air. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Containers can burst violently or explode when heated, due to excessive pressure build-up.
-------------------------	--

5.3. Advice for firefighters

Protective actions during firefighting	Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours. Warn firefighters that aerosols are involved.
---	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate. Avoid inhalation of vapours.
-----------------------------	--

6.2. Environmental precautions

Environmental precautions	Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material.
----------------------------------	---

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion.
--------------------------------	--

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8. For waste disposal, see Section 13.
------------------------------------	---

SECTION 7: Handling and storage

Sterling Engine Degreaser

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Do not spray on a naked flame or any incandescent material.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Store at moderate temperatures in dry, well ventilated area. Extremely flammable. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Storage class Flammable compressed gas storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Appropriate engineering controls Provide adequate ventilation. Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients.

Personal protection Do not eat, drink or smoke when using the product.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

Hand protection Due to the packaging form, aerosol, risk of skin contact is small. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

Hygiene measures Wash hands after handling. Wash promptly if skin becomes contaminated. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Use appropriate skin cream to prevent drying of skin.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Colour White/off-white.

Odour Organic solvents.

Initial boiling point and range -40 to -2°C @ 1013 hPa

Flash point <-40°C

Sterling Engine Degreaser

Upper/lower flammability or explosive limits	Lower : 1.8% - Upper 9.5%
Vapour pressure	ca. 590 to 1760 kPa @ 45°C
Vapour density	ca. 1.5 at 15°C
Partition coefficient	log Pow: ca. 2.3 to 2.8
Auto-ignition temperature	410-580°C
Comments	Information given is applicable to the major ingredient.

9.2. Other information

Other information	Not available.
Volatile organic compound	This product contains a maximum VOC content of 630 g/l.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Stable at normal ambient temperatures and when used as recommended.
-------------------	---

10.2. Chemical stability

Stability	Avoid the following conditions: Heat, sparks, flames.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Does not decompose when used and stored as recommended.
---	---

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.
----------------------------	--

10.5. Incompatible materials

Materials to avoid	Keep away from oxidising materials, heat and flames.
---------------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours.
---	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg)	55,555.56
-------------------------	-----------

General information	Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.
----------------------------	---

Inhalation	Vapours in high concentrations are narcotic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. Unconsciousness, possibly death.
-------------------	--

Skin contact	Skin irritation should not occur when used as recommended. Repeated exposure may cause skin dryness or cracking.
---------------------	--

Sterling Engine Degreaser

Eye contact	Vapour or spray in the eyes may cause irritation and smarting.
Acute and chronic health hazards	Arrhythmia (deviation from normal heartbeat) Narcotic effect. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Prolonged or repeated exposure to vapours in high concentrations may cause the following adverse effects: Nausea, vomiting. Headache.
Route of entry	Inhalation
Target organs	Central nervous system Respiratory system, lungs
Medical symptoms	Arrhythmia (deviation from normal heart beat). Narcotic effect. Vapours may cause drowsiness and dizziness.

SECTION 12: Ecological Information

Ecotoxicity	This product has not been tested but contains ingredients which are toxic or very toxic to aquatic organisms and may cause long term adverse effects in the aquatic environment. During normal use the volatility of the components and the packaging form, pressurised container, make entry into the aquatic environment unlikely, however, do not empty or discharge into drains or watercourses. Ensure container is empty before disposal to prevent contents entering watercourses.
--------------------	---

12.1. Toxicity

Toxicity	Not available.
-----------------	----------------

12.2. Persistence and degradability

Persistence and degradability	Not available.
--------------------------------------	----------------

12.3. Bioaccumulative potential

Bioaccumulative potential	Not available.
----------------------------------	----------------

Partition coefficient	log Pow: ca. 2.3 to 2.8
------------------------------	-------------------------

12.4. Mobility in soil

Mobility	Not known.
-----------------	------------

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	Not available.
---	----------------

12.6. Other adverse effects

Other adverse effects	Not available.
------------------------------	----------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Do not puncture or incinerate, even when empty.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Empty containers must not be punctured or incinerated because of the risk of an explosion.

SECTION 14: Transport information

Sterling Engine Degreaser

General

This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities. Aerosols not so packed and labelled must show the following.

14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

Transport labels



14.4. Packing group

ADR/RID packing group	None
IMDG packing group	None
ADN packing group	None
ICAO packing group	None

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

Sterling Engine Degreaser

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EU legislation	Commission Regulation (EU) No 453/2010 of 20 May 2010.
Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131. British Aerosol Manufacturers Code of Practice 7th. Edition 1999

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	Revised classification.
Revision date	10/08/2016
Revision	4
SDS number	12914
SDS status	Approved.
Risk phrases in full	R10 Flammable. R12 Extremely flammable. R22 Harmful if swallowed. R41 Risk of serious damage to eyes. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed.
Hazard statements in full	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated H280 Contains gas under pressure; may explode if heated. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H318 Causes serious eye damage. H319 Causes serious eye irritation. H372 Causes damage to organs through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.