### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME: LS95 - DRY FILM LUBE

**SUPPLIER** Beal UK Ltd

Sterling Works Texas Street Tingley (A650) Leeds LS27 0HG

0113 253 8888 sales@beal.org.uk

### Container size 400ml

#### **2 HAZARDS IDENTIFIED**

## PHYSICAL AND CHEMICAL HAZARDS

Extremely flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness or dizziness.

**ENVIRONMENTAL HAZARDS** 

#### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification	
Acetone	200-662-2	67-64-1	50-55%	R11, R36,R66, R67	
Xylene	601-022-00-9	95-47-6	1-5%	R10 Xn; R20/21 Xi; R38	
Mixed Aromatic Hydrocarbons	649-356-00-4	64742-95-6	1-5%	R10 Xn; R37 R65 R66 R67 N; R51/53	
PTFE				N/A	
Butane	106-97-8	203-448-7	10-20%	F+; R12	
Propane	74-98-6	200-827-9	10-20%	F+; R12	
The Full Text for all R-Phrases are displayed in Section 16					

# **4 FIRST AID MEASURES**

# **GENERAL INFORMATION**

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

#### INHAI ATION

Move the exposed person to fresh air at once. Get medical attention. Provide rest, warmth and fresh air. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

#### **INGESTION**

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Drink plenty of water. Get medical attention immediately. Provide rest and, warmth and fresh air.

# SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention promptly if symptoms occur after washing.

#### **EYE CONTACT**

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

### **5 FIRE-FIGHTING MEASURES**

#### **EXTINGUISHING MEDIA**

Fire can be extinguished using: Foam, Carbon Dioxide (C02), Dry Powder. DO NOT USE water jet.

### SPECIFIC HAZARDS

Fire may produce dense black smoke containing hazardous combustion products (see Section 10). Decomposition products may be a hazard to health. Do not allow run-off from fire fighting to enter drains or water courses.

### PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

### **6 ACCIDENTAL RELEASE MEASURES**

#### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

# **ENVIRONMENTAL PRECAUTIONS**

Avoid discharge into drains, water courses or onto the ground.

DO NOT allow to enter drains or watercourses. If the product enters drains or sewers, the local water company should be informed immediately. In the case of contamination of streams, rivers or lakes, inform the relevant environment Agency. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixture with air.

# SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb spillage with non-combustible, absorbent material. Collect spillage in containers, seal securely and deliver for disposal accordingly to local regulations. Do not contaminate water sources or sewer.

### **7 HANDLING AND STORAGE**

# **USAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Do not use sparking tools around aerosols. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours and spray mist, for personal protection, see Section 8. Use approved respirator if air contamination is above accepted level. Never apply pressure to the aerosol as it is a pressurised object and may explode if pressure is applied.

## STORAGE PRECAUTIONS

Observe label precautions. Store between 5-25°C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Store separately from oxidising agents and strongly alkaline/acidic materials.

### **8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	TWA – 8hrs	STEL – 15mins	Notes
Acetone	OEL	1210mg m <sup>-3</sup>	3620 mg m <sup>-3</sup>	
Xylene	OEL	220mg m <sup>-3</sup>	441 mg m <sup>-3</sup>	
Butane	OEL	1450mg m <sup>-3</sup>	1810 mg m <sup>-3</sup>	
Propane	OEL	1000ppm	2500ppm	





### **8 EXPOSURE CONTROLS/PERSONAL PROTECTION - CONTINUED**

#### **ENGINEERING MEASURES**

Provide adequate general and local exhaust ventilation.

### RESPIRATORY EQUIPMENT

If ventilation is insufficient, suitable respiratory protection must be provided. Wear mask supplied with: Gas cartridges suitable for organic substances.

### HAND PROTECTION

Use protective gloves.

### **EYE PROTECTION**

Wear approved safety goggles.

#### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Provide eyewash station.

### HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA. Wash at the end of each shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

# 9 PHYSICAL AND CHEMICAL PROPERTIES

FORM: Aerosol

FLASHPOINT: Not known for blend

COLOUR: Clear ODOUR: Aromatic

#### 10 STABILITY AND REACTIVITY

STABILITY: Stable under the recommended storage and handling conditions

in Section 7.

CONDITIONS TO AVOID: Applying heat or pressure to the aerosol may result in explosion

And fire. Naked flames, smoking, wet and damp storage

conditions and mishandling may also result in explosion and fire.

MATERIALS TO AVOID: Keep away from oxidising agents, strong alkaline/acidic materials

in order to avoid exothermic reactions.

HAZARDOUS DECOMPOSITION PRODUCTS: In a fire, hazardous decomposition products such as smoke,

carbon monoxide, carbon dioxide and oxides of nitrogen may be

produced.

# 11 TOXICOLOGICAL INFORMATION

ACUTE TOXICITY: Gas or vapour is harmful on prolonged contact or in high concentration. This product can

be hazardous when inhaled and/or touched. Irritant to eyes and mucous membranes.

LOCAL EFFECTS: Hazardous in case of skin contact, irritant.

CHRONIC TOXICITY: Repeated exposure may cause chronic eye irritation. May cause chemical eye burns.

Swallowing concentrated chemical may cause severe internal injury, unconsciousness

and death.

Contains no known category 1 or 2 carcinogens, mutagens or reproductive toxicants.

REVISION DATE: 31/01/2012 DRY FILM LUBE

## 12 ECOLOGICAL INFORMATION

MOBILITY: The product is gaseous and will quickly dissipate and break down in air.

PERSISTANCE AND DEGRADABILITY: The majority of this product is inherently biodegradable, oxidising rapidly

by photochemical reactions in air. The remaining chemicals degrade in soil to form smaller molecules, which are either biodegraded in soil or

volatised into the air.

BIO ACCUMULATION: This product has the potential to bio accumulate.

ECOTOXICITY: This product is not classified as harmful to the environment.

#### 13 DISPOSAL CONSIDERATIONS

# **GENERAL INFORMATION**

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

### **DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

### 14 TRANSPORT INFORMATION

UN NUMBER: UN1950 SHIPPING NAME: Aerosols


HAZARD CLASS: 2.1 (for Sea Transport). Classification code 5F

EmS: F-D, S-U CLASS: 2 LABELLING: 2.1

### 15 REGULATORY INFORMATION

# LABELLING:







Irritant

**RISK PHRASES** 

R12 Extremely flammable R36 Irritating to eyes

R66 Repeated exposure may cause skin dryness or cracking

R67 Vapours may cause drowsiness and dizzinesss

SAFETY PHRASES S2 Keep out of the reach of children

S16 Keep away from sources of ignition – no smoking

S23 Do not breathe gas/fumes/vapour/spray

S25 Avoid contact with eyes

S26 In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

S35 This material and its container must be disposed of in a safe way

S36 Wear suitable protective clothing

No chemical safety assessments have been carried out for any of the substances used in this preparation.

REVISION DATE: 31/01/2012

DRY FILM LUBE

### **16 OTHER INFORMATION**

USES ADVISED AGAINST: The product should not be used for any other purpose other than its intended use.

Handling, storage and conditions to avoid instructions must be followed at all times.

The information contained in this safety data sheet is provided in accordance with the requirements of the Chemical (Hazard Information and Packaging) Regulations. The information we have provided is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not considered a warranty or quality specification. The information relates only to the material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.