

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/3

SOL7 Telux Milder

Soldering Flux

Revision 0

Revision date 2012-04-30

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	SOL7 Telux Milder Soldering Flux
--------------	----------------------------------

1.3. Details of the supplier of the safety data sheet


Company	Beal UK Limited
Address	Sterling Works Texas Street Tingley, Leeds LS27 0HG United Kingdom
Web	www.beal.org.uk
Telephone	+44 (0) 113 253 8888
Fax	+44 (0) 800 357 650
Email	sales@beal.org.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/E C	N; R51/53 Symbols: N: Dangerous for the environment.
Main hazards	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Symbols	The product is classified in accordance with 67/548/EEC. N: Dangerous for the environment. 
Risk phrases	R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Safety phrases	S29 - Do not empty into drains.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Zinc chloride (Zinc chloride, fume)	030-003-00-2	7646-85-7	231-592-0		1 - 10%	C; R34 Xn; R22 N; R50/53
Ammonium chloride (Ammonium chloride, fume)	017-014-00-8	12125-02-9	235-186-4		0 - 0.5%	Xn; R22 Xi; R36

Telux Milder Soldering Flux

Revision 0

Revision date 2012-04-30

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Toxic by inhalation. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Inhalation of vapour may cause shortness of breath. Move the exposed person to fresh air. Seek medical attention.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Toxic in contact with skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention.
Ingestion	Toxic if swallowed. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. If swallowed, seek medical advice immediately and show this container or label. DO NOT INDUCE VOMITING.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Carbon oxides. Alcohol resistant foam.
--	--

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Wear: Self-contained breathing apparatus. Wear chemical protective clothing.
--	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Wear suitable protective equipment.
--	---

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area.
--	--

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.
--	--

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Ammonium chloride (Ammonium chloride, fume)	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m ³ : 10
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m ³ : 20
Zinc chloride (Zinc chloride, fume)	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m ³ : 1
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m ³ : 2

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
---	--

Telux Milder Soldering Flux

Revision 0

Revision date 2012-04-30

8.2. Exposure controls

8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Self-contained breathing apparatus must be used in handling.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State	Gel
Colour	Brown
Odour	Mild

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

SECTION 11: Toxicological information

11.1.4. Toxicological Information

	No data is available on this product.
--	---------------------------------------

SECTION 12: Ecological information

12.1. Toxicity

	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
--	---

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

SECTION 14: Transport information

Further information

	The product is not classified as dangerous for carriage.
--	--

SECTION 15: Regulatory information

SECTION 16: Other information

Other information

Text of risk phrases in Section 3	R22 - Harmful if swallowed. R34 - Causes burns. R36 - Irritating to eyes. R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
-----------------------------------	--

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--