


Cable Lugs - Flared Entry

Material:

- o Terminal Body: Copper
- o Plating: Tin



Cable Lugs - Flared Entry

Item No.	Cable size sq.mm	Hole Dia. E	A	C	D	F	G	H	B	J
R6-5	6	5.2	3.8	5.5	10	1.2	5	6	9	23
R6-6	6	6.5	3.8	5.5	10	1.2	5	6	9	23
R6-8	6	8.2	3.8	5.5	12	1	6	9	9	27
R10-5	10	5.2	4.5	6.2	12	1.2	6	7	14	30
R10-6	10	6.5	4.5	6.2	12	1.2	6	7	14	30
R10-8	10	8.2	4.5	6.2	12	1.2	6	9	12	30
R10-10	10	10.5	4.5	6.2	15	1.4	8.5	10.5	12	34
R10-12	10	12.7	4.5	6.2	15	1.4	8.5	10.5	12	34
R16-5	16	5.2	5.4	7.1	12	1.4	7	7	12	30
R16-6	16	6.5	5.4	7.1	12	1.4	7	7	12	30
R16-8	16	8.2	5.4	7.1	12	1.4	7	9	12	32
R16-10	16	10.5	5.4	7.1	15	1.0	8	12	12	36
R16-12	16	12.7	5.4	7.1	16	1.0	8	12	12	36
R25-6	25	6.5	6.8	8.8	13	2	6	7	16	32.2
R25-8	25	8.2	6.8	8.8	13	2	6	7	16	32.2
R25-10	25	10.5	6.8	8.8	16	1.6	9	11	14	37
R25-12	25	12.7	6.8	8.8	18	1.2	11	13	14	37
R35-6	35	6.5	8.2	10.6	15	2.4	9	9	14	35
R35-8	35	8.2	8.2	10.6	15	2.4	9	9	14	35
R35-10	35	10.5	8.2	10.6	15	2.4	9	9	21.5	41.5
R35-12	35	12.7	8.2	10.6	18	2.0	9	9	21.5	41.5
R50-6	50	6.5	9.5	12.4	18	2.9	10	11	19	43
R50-8	50	8.2	9.5	12.4	18	2.9	10	11	19	43
R50-10	50	10.5	9.5	12.4	18	2.9	10	11	19	43
R50-12	50	12.7	9.5	12.4	18	2.9	10	11	19	43
R70-6	70	6.5	11.2	14.7	21	3.5	12	13	21	50
R70-8	70	8.2	11.2	14.7	21	3.5	12	13	21	50
R70-10	70	10.5	11.2	14.7	21	3.5	12	13	21	50
R70-14	70	14.7	11.2	14.7	21	3.5	12	13	21	50
R70-12	70	12.7	11.2	14.7	21	3.5	12	13	21	50
R70-16	70	17.0	11.2	14.7	21	3.5	12	13	21	50
R95-8	95	8.4	13.5	17.4	25	3.9	13	13	23	55
R95-10	95	10.5	13.5	17.4	25	3.9	13	13	23	55
R95-12	95	12.7	13.5	17.4	25	3.9	13	13	23	55
R95-14	95	14.7	13.5	17.4	25	3.9	13	13	23	55
R95-16	95	17.0	13.5	17.4	25	3.9	13	13	23	55
R120-8	120	8.2	15.0	19.4	28	4.4	14	14	25	60
R120-10	120	10.5	15.0	19.4	28	4.4	14	14	25	60
R120-12	120	12.7	15.0	19.4	28	4.4	14	14	25	60
R120-14	120	14.7	15.0	19.4	28	4.4	14	14	25	60
R150-10	150	10.5	16.5	21.2	30	4.7	16	16	30	69
R150-12	150	12.7	16.5	21.2	30	4.7	16	16	30	69
R150-14	150	14.7	16.5	21.2	30	4.7	16	16	30	69
R150-16	150	17.0	16.5	21.2	30	4.7	16	16	30	69
R185-10	185	10.5	18.5	23.5	34	5.0	17	17	36	78
R185-12	185	13.0	18.5	23.5	34	5.0	17	17	36	78
R185-14	185	14.7	18.5	23.5	34	5.0	17	17	36	78
R185-16	185	17.0	18.5	23.5	34	5.0	17	17	36	78
R240-12	240	13.0	21.0	26.5	38	5.5	20	20	42	92
R240-14	240	14.7	21.0	26.5	38	5.5	20	20	42	92
R240-16	240	17.0	21.0	26.5	38	5.5	20	20	42	92