SAFETY DATA SHEET Screenwash

SECTION 1: Identification of th	ne substance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	Screenwash
Product number	Jan19 - Jan20
1.2. Relevant identified uses of	f the substance or mixture and uses advised against
Identified uses	Screenwash concentrate
1.3. Details of the supplier of the	ne safety data sheet
Supplier	Beal (UK) Ltd Sterling Works Texas Street Tingley (A650) Leeds, West Yorkshire LS27 0HG T 0113 253 8888 F 0113 253 0223 sales@beal.org.uk
1.4. Emergency telephone nun	nber
Emergency telephone	0113 253 8888
SECTION 2: Hazards identification	ation
2.1. Classification of the substa	ance or mixture
Classification Physical hazards	Flam. Liq. 3 - H226
Health hazards	Not Classified
Environmental hazards	Not Classified
Classification (67/548/EEC or 1999/45/EC)	R10.
Physicochemical	This product is flammable and burning product will liberate carbon dioxide and possibly carbon monoxide.
2.2. Label elements Pictogram	
Signal word	Warning
Hazard statements	H226 Flammable liquid and vapour.
Precautionary statements	 P102 Keep out of reach of children. P271 Use only outdoors or in a well-ventilated area. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P313 Get medical advice/attention. P501 Dispose of contents/container in accordance with local regulations.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

PROPAN-2-OL			5-10%	
CAS number: 67-63-0	EC number: 200-661-7	REACH registration number: 01- 2119457558-25		
Classification	Classificatio	on (67/548/EEC or 1999/45/EC)		
Flam. Liq. 2 - H225	F;R11 Xi;R	F;R11 Xi;R36 R67		
Eye Irrit. 2 - H319				
STOT SE 3 - H336				
SODIUM HYDROXIDE			<19	
SODIUM HYDROXIDE CAS number: 1310-73-2	EC number: 215-185-5	REACH registration number: 01-	<19	
	EC number: 215-185-5	REACH registration number: 01- 2119457892-27	<19	
CAS number: 1310-73-2		2119457892-27	<19	
	Classificatio	-	<19	
CAS number: 1310-73-2		2119457892-27	<19	

4.1. Description of first aid measures			
General information	Move affected person to fresh air at once.		
Inhalation	Remove person to fresh air and keep comfortable for breathing. Move into fresh air and keep at rest. Get medical attention if any discomfort continues.		
Ingestion	Immediately rinse mouth and provide fresh air. Do not induce vomiting. Get medical attention.		
Skin contact	Wash skin thoroughly with soap and water. Remove contaminated clothing and rinse skin thoroughly with water.		
Eye contact	Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Continue to rinse for at least 15 minutes and get medical attention.		
4.2. Most important symptoms and effects, both acute and delayed			
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.		
4.3. Indication of any immediate medical attention and special treatment needed			
Notes for the doctor	Treat symptomatically.		
SECTION 5: Firefighting measures			
5.1. Extinguishing media			

Suitable extinguishing media Foam. Dry chemicals. Water spray.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours. The product is flammable.		
5.3. Advice for firefighters			
Protective actions during firefighting	Use water to keep fire exposed containers cool and disperse vapours. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Water spray may be used to flush spills away from exposures and dilute spills to non-flammable mixtures. Use water spray to reduce vapours.		
SECTION 6: Accidental release	se measures		
6.1. Personal precautions, pro	stective equipment and emergency procedures		
Personal precautions	Provide adequate ventilation. If ventilation is inadequate, suitable respiratory protection must be worn. Avoid inhalation of vapours and contact with skin and eyes.		
6.2. Environmental precaution	<u>s</u>		
Environmental precautions	Avoid discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.		
6.3. Methods and material for	containment and cleaning up		
Methods for cleaning up	Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses.		
6.4. Reference to other sectio	ns		
Reference to other sections	For personal protection, see Section 8. For waste disposal, see Section 13.		
SECTION 7: Handling and sto	prage		
7.1. Precautions for safe hand	lling		
Usage precautions	Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. Use good earthing procedures when decanting from container.		
7.2. Conditions for safe storage, including any incompatibilities			
Storage precautions	Keep away from oxidising materials, heat and flames. Store at moderate temperatures in dry, well ventilated area. Keep away from heat, sparks and open flame.		
7.3. Specific end use(s)			
Specific end use(s)	The identified uses for this product are detailed in Section 1.2.		
SECTION 8: Exposure Controls/personal protection			
8.1. Control parameters Occupational exposure limits			

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³ Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

SODIUM HYDROXIDE

Short-term exposure limit (15-minute): WEL 2 mg/m³ WEL = Workplace Exposure Limit

Ingredient comments	WEL = Workplace Exposure Limits		
PROPAN-2-OL (CAS: 67-63-0)			
DNEL	Industry - Dermal; Long term systemic effects: 888 mg/kg/day Industry - Inhalation; Long term systemic effects: 500 mg/m³ Consumer - Dermal; Long term systemic effects: 319 mg/kg/day Consumer - Dermal; Long term systemic effects: 26 mg/kg/day Consumer - Inhalation; Long term systemic effects: 89 mg/m³		
PNEC	 Fresh water; 140.9 mg/l Marine water; 140.9 mg/l Intermittent release; 140.9 mg/l Sediment (Freshwater); 552 mg/kg Sediment (Marinewater); 552 mg/kg STP; 2251 mg/l Soil; 28 mg/kg 		
A	lcohols, C12-14, ethoxylated (1-2,5 EO), sulphates, sodium salts (CAS: 68891-38-3)		
DNEL	Industry - Dermal; Long term systemic effects: 2750 mg/kg/day Industry - Inhalation; Long term systemic effects: 175 mg/m³ Consumer - Oral; Long term systemic effects: 15 mg/kg/day Consumer - Dermal; Long term systemic effects: 1650 mg/kg/day Consumer - Inhalation; Long term systemic effects: 52 mg/m³		
PNEC	 Fresh water; 0.24 mg/l Marine water; 0.024 mg/l Intermittent release; 0.071 mg/l Sediment; 5.45 mg/kg Marine water; 0.545 mg/kg Soil; 0.946 mg/kg STP; 10 g/L 		
	SODIUM HYDROXIDE (CAS: 1310-73-2)		
DNEL	Consumer - Inhalation; Long term local effects: 1 mg/m ³ Industry - Inhalation; Long term local effects: 1 mg/m ³		
8.2. Exposure controls			
Appropriate engineering controls	Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.		
Personal protection	When using do not smoke		
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.		
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn in a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.		
Hygiene measures	Wash hands at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke.		

Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn.		
SECTION 9: Physical and Chemical Properties			
9.1. Information on basic physical and chemical properties			
Appearance	Clear liquid.		
Colour	Blue.		
Odour	Slight alcoholic.		
Flash point	32°C CC (Closed cup).		
Relative density	0.969 @ °C		
Solubility(ies)	Soluble in water.		
Comments	Information given is applicable to the major ingredient.		
9.2. Other information			
Other information	Not available.		
Volatile organic compound	This product contains a maximum VOC content of 50 g/l.		
SECTION 10: Stability and re	activity		
10.1. Reactivity			
Reactivity	Stable at normal ambient temperatures and when used as recommended.		
10.2. Chemical stability			
Stability	Stable at normal ambient temperatures and when used as recommended.		
10.3. Possibility of hazardous reactions			
Possibility of hazardous reactions	Does not decompose when used and stored as recommended.		
10.4. Conditions to avoid			
Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Oxidising agents. Reducing agents.		
10.5. Incompatible materials			
Materials to avoid	Keep away from oxidising materials, heat and flames.		
10.6. Hazardous decompositi	on products		
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours.		
SECTION 11: Toxicological information			
11.1. Information on toxicological effects			
Inhalation	Vapours may irritate throat/respiratory system. A single exposure may cause the following adverse effects: Coughing, Difficulty in breathing		

	adverse effects: Coughing. Difficulty in breathing.
Ingestion	May cause discomfort if swallowed.
Skin contact	Skin irritation should not occur when used as recommended. Repeated exposure may cause skin dryness or cracking.

Screenwash

Eye contact	Irritating to eyes. Vapour or spray in the eyes may cause irritation and smarting. Repeated exposure may cause chronic eye irritation.	
Acute and chronic health hazards	Irritating to eyes.	
Route of entry	Inhalation	
Target organs	Central nervous system Respiratory system, lungs	
Medical symptoms	Arrhythmia (deviation from normal heart beat).	
SECTION 12: Ecological Info	mation	
Ecotoxicity	Not regarded as dangerous for the environment.	
12.1. Toxicity		
Toxicity	Not available.	
12.2. Persistence and degrad	ability	
Persistence and degradability	Not available.	
12.3. Bioaccumulative potenti		
Bioaccumulative potential	Not available.	
12.4. Mobility in soil		
Mobility	Not known.	
12.5. Results of PBT and vPv	B assessment	
Results of PBT and vPvB assessment	Not available.	
12.6. Other adverse effects		
Other adverse effects	Not available.	
SECTION 13: Disposal consid	derations	
13.1. Waste treatment method	ds	
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Avoid the spillage or runoff entering drains, sewers or watercourses.	
SECTION 14: Transport information		
General	Packs of 5L and under are not regulated under the Limited Quantities Provisions.	
14.1. UN number		
UN No. (ADR/RID)	1993	
UN No. (IMDG)	1993	
UN No. (ICAO)	1993	
14.2. UN proper shipping nam		
Proper shipping name (ADR/RID)	FLAMMABLE LIQUID, N.O.S. (PROPAN-2-OL)	
Proper shipping name (IMDG)	FLAMMABLE LIQUID, N.O.S. (PROPAN-2-OL)	

Proper shipping name	(ICAO)	FLAMMABLE LIQUID, N.O.S. (PROPAN-2-OL)

Proper shipping name (ADN) FLAMMABLE LIQUID, N.O.S. (PROPAN-2-OL)

14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID label	3
IMDG class	3
ICAO class/division	3

Transport labels



14.4. Packing group	
ADR/RID packing group	III
IMDG packing group	Ш
ICAO packing group	Ш
14.5. Environmental hazards	

Environmentally hazardous substance/marine pollutant No.

14.6. Special precautions	for user
EmS	F-E, S-D

Emergency Action Code	•3Y
Hazard Identification Number (ADR/RID)	30

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture			
National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).		
EU legislation	Commission Regulation (EU) No 453/2010 of 20 May 2010.		
Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131. British Aerosol Manufacturers Code of Practice 7th. Edition 1999		

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments Revision date Revision	Supplemental information added. 18/11/2015 2
SDS number	12671
Risk phrases in full	R10 Flammable. R11 Highly flammable. R36 Irritating to eyes. R67 Vapours may cause drowsiness and dizziness.
Hazard statements in full	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.