



SAFETY DATA SHEET

LS153- PETROL INJECTOR CLEANER

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY

PRODUCT NAME: LS153 - PETROL INJECTOR CLEANER

PART No.: LS152

SUPPLIER: Beal UK Ltd
Sterling Works, Texas St,
Tingley (A650), Leeds,
LS27 OHG

TEL: 0113 253 8888

EMERGENCY TELEPHONE(S): TEL: 01708 335553 FAX: 01708 340654

2 COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME	EINECS No.	CAS No.	CONTENTS	SYMBOL	RISK (R No.)
Odourless Kerosene		64742-47-8	60-100 %	Xn	65, 66
FUEL ADDITIVE			30-60 %	F, Xn	65, 66

The full text for all R-phrases are shown in section 16.

3 HAZARDS IDENTIFICATION

Harmful: may cause lung damage if swallowed.
Repeated exposure may cause skin dryness or cracking.

4 FIRST AID MEASURES

INHALATION: Remove victim immediately from source of exposure. Provide rest, warmth and fresh air.

INGESTION: If swallowed, do not induce vomiting. Seek medical advice immediately and show the container or label.

SKIN: Wash the skin immediately with soap and water.

EYES: Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Powder, foam or CO₂.

SPECIAL FIRE FIGHTING PROCEDURES: Breathing apparatus should be worn if exposure to fumes is likely. Use water to keep fire exposed containers cool and disperse vapours.

UNUSUAL FIRE & EXPLOSION HAZARDS: Solvent vapours may form explosive mixtures with air.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEANUP METHODS: Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb material from ruptured or leaking containers onto an inert - material. Transfer to suitable container for subsequent disposal.

PETROL INJECTOR CLEANER

7 HANDLING AND STORAGE

USAGE PRECAUTIONS: Avoid spilling, skin and eye contact.
STORAGE PRECAUTIONS: Store in a cool dry place away from all sources of heat including direct sunlight.

8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

INGREDIENT NAME	CAS No	STD	LT EXP (8 hrs)	ST EXP (15 min)
Odourless Kerosene	64742-47-8	OES	1200 mg/m ³	3600 mg/m ³

INGREDIENT COMMENTS: OES = Occupational Exposure Standard.

PROTECTIVE EQUIPMENT:



PROTECTIVE GLOVES: Chemical resistant gloves required for prolonged or repeated contact.
EYE PROTECTION: Wear approved chemical safety goggles where eye exposure is reasonably probable.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Liquid	COLOUR:	Dark. Straw
ODOUR/TASTE:	Petroleum.		
SPECIFIC GRAVITY (Water=1):	0.828±0.01 @ 25 °C		

10 STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Avoid heat, flames and other sources of ignition.
MATERIALS TO AVOID: Strong oxidizing agents.
HAZARDOUS DECOMPOSITION PRODUCTS: Fire or high temperatures create: Carbon dioxide (CO₂). Carbon monoxide (CO).

11 TOXICOLOGICAL INFORMATION

INHALATION: High concentrations of vapour may cause dizziness, nausea and headaches
INGESTION: May cause irritation of mouth, respiratory tract and intestinal system.
SKIN: Prolonged or repeated exposure may cause severe irritation.
EYES: May cause mild irritation or discomfort.

12 ECOLOGICAL INFORMATION

ENVIRONMENTAL HAZARDS: Not classified as dangerous to the environment.
ACUTE FISH TOXICITY: Not toxic to aquatic species.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS: Dispose of in accordance with local authority requirements.

14 TRANSPORT INFORMATION

GENERAL: NOT CLASSIFIED FOR TRANSPORT
LABEL FOR CONVEYANCE: No transport warning sign required.

ROAD:
RAIL:
SEA:
AIR:

PETROL INJECTOR CLEANER

15 REGULATORY INFORMATION

LABEL FOR SUPPLY:



HARMFUL

RISK PHRASES:	R-65	Harmful: may cause lung damage if swallowed.
	R-66	Repeated exposure may cause skin dryness or cracking.
SAFETY PHRASES:	S-35	This material and its container must be disposed of in a safe way.
	S-37	Wear suitable gloves.
	S-62	If swallowed, do not induce vomiting. Seek medical advice immediately and show the container or label.

16 OTHER INFORMATION

USER NOTES:	This preparation requires a formal COSHH assessment which should ensure that employees are aware of the hazards/precautions detailed in this data sheet. The COSHH assessment should also ensure that recommended safety equipment is available and, where applicable, the exposure limits detailed in section 8 are not being exceeded.	
SDS No.:	0253L	
R-PHRASES (Full Text):	R-66	Repeated exposure may cause skin dryness or cracking.
	R-65	Harmful: may cause lung damage if swallowed.
DATE:	17/09/2010	

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS, TO THE BEST OF THE COMPANY'S KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE INDICATED. HOWEVER, NO WARRANTY, GUARANTEE OR REPRESENTATION IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABILITY OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE.